

| | L # | Hits | Search Text | DBs |
|---|-----|------|---|---|
| 1 | L1 | 346 | 725/111.ccls. | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 2 | L2 | 68 | 1 AND ((@ad <= "19990205") or (@rlad <= "19990205")). | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 3 | L3 | 7647 | (1 or "cable modem") AND ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral)) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 4 | L4 | 983 | 3 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 5 | L5 | 28 | 2 AND ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral)) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 6 | L6 | 309 | 4 AND (encrypt\$3) AND (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 7 | L7 | 4 | 5 AND (encrypt\$3) AND (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |

| | L # | Hits | Search Text | DBs |
|----|-----|------|---|---|
| 8 | L8 | 920 | ("cable modem") SAME ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral)) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 9 | L9 | 245 | 8 AND (encrypt\$3) AND (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 10 | L10 | 28 | 9 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 11 | L11 | 775 | ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral)) WITH (encrypt\$3 "key ID") WITH (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 12 | L12 | 128 | 11 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 13 | L13 | 1098 | 348/734.ccls. | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 14 | L14 | 461 | 13 AND ((@ad <= "19960430") or (@rlad <= "19960430")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |

| | L # | Hits | Search Text | DBs |
|----|-----|------|---|---|
| 15 | L15 | 44 | ("5710605").URPN. | USPAT |
| 16 | L16 | 3 | ("5410326" "5410367" "5532754").PN. | US-PGPUB; USPAT; USOCR |
| 17 | L17 | 93 | ((assign\$4 creat\$3 generat\$3) NEAR5 ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral))) WITH (encrypt\$3 "key ID") WITH (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 18 | L18 | 12 | 17 AND ((@ad <= "19960430") or (@rlad <= "19960430")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 19 | L19 | 5848 | ((assign\$4 creat\$3 generat\$3) NEAR5 ((MAC network client terminal unique) NEAR2 (address identif\$5 number numeral))) WITH (headend "head end" server provider "central office") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 20 | L20 | 345 | 19 AND ((@ad <= "19960430") or (@rlad <= "19960430")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 21 | L21 | 6756 | ((assign\$4 creat\$3 generat\$3) NEAR5 ((MAC network client terminal unique) NEAR2 (address identif\$5 number ID))) WITH (headend "head end" server provider "central office") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 22 | L22 | 379 | 21 AND ((@ad <= "19960430") or (@rlad <= "19960430")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |

| | L # | Hits | Search Text | DBs |
|----|-----|------|--|--|
| 23 | L23 | 1446 | 21 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 24 | L24 | 980 | 21 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | USPAT |
| 25 | L25 | 691 | 24 NOT 22 | USPAT |
| 26 | L26 | 102 | 21 SAME (encrypt\$3) SAME (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 27 | L27 | 20 | 26 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |
| 28 | L28 | 1485 | ((encrypt\$3 key) NEAR5 ((MAC network client terminal unique) NEAR2 (address identif\$5 number ID))) WITH (headend "head end" server provider "central office") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 29 | L29 | 271 | 28 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |

| | L # | Hits | Search Text | DBs |
|----|-----|------|--|--|
| 30 | L30 | 27 | ((encrypt\$3 key) NEAR5 ((MAC network client terminal unique) NEAR2 (address identif\$5 number ID))) WITH cookie WITH (headend "head end" server provider "central office") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 31 | L31 | 9 | 30 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |
| 32 | L32 | 424 | cookie SAME (encrypt\$3) SAME (authenticat\$3 authoriz\$5) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 33 | L33 | 50 | 32 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |
| 34 | L34 | 1446 | 21 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |
| 35 | L35 | 334 | ((assign\$4 creat\$3 generat\$3) NEAR5 ((MAC) NEAR2 (address identif\$5 number ID))) WITH (headend "head end" server provider "central office") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |

| | L # | Hits | Search Text | DBs |
|----|-----|------|---|--|
| 36 | L36 | 54 | 35 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |
| 37 | L37 | 83 | "6182142" | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB |
| 38 | L38 | 18 | 37 AND ((@ad <= "19990205") or (@rlad <= "19990205")) | US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB |